

Nordic Stories

Isograd (Cushion)

MODULAR TILE & PLANK

Construction	Tufted, Textured Loop
Tile Sizes	50cm x 50cm 25cm x 1m
Yarn Type	Universal® Fibers Solution-Dyed Nylon Type 6,6
Stain Repel / Stain Resist / Soil Release	StainSmart®
Antimicrobial	AlphaSan® AF Built-In Protection†
Dye Method	Solution Dyed
Tufted Face Weight	17 oz/yd ² (575g/m ²)
Gauge	1/12
Stitches Per Inch	10.4
Tufts	124.8/in ² (1,933/100 cm ²)
Finished Pile Height	0.13" (3.30 mm)
Standard Backing	Underscore™ Cushion Backing
Recycled Content by Total Weight	Up to 42.3% Pre-Consumer, Up to 10.8% Post-Consumer,
Nominal Total Thickness	0.30" (7.6 mm)
Nominal Total Weight	98 oz/yd ² (3,323 g/m ²)
Flammability (Radiant Panel Test)	CRF= 7.7 Kw/m ² . Smoke= 222%.min
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV
Recommended Maintenance	MilliCare® - Refer to the Ontera Cleaning & Maintenance guide or Millicare® Australia Pass (ISO10580:2010)
Indoor Air Quality	Commercial Extra Heavy Duty & Stairs (CEHDS)
ACCS Grading	Level 4 (Certificate No. 16108)
ECS Grading	15 year Wear Warranty
Applicable Warranties	15 year Dimensional Stability warranty 15 year Anti-Static Warranty 15 Year Castor Chair Wear Warranty
Recommended Installation Method(s)	Brick (Horizontal) & Monolithic for Tiles Ashlar (Vertical) & Herringbone for Planks



Ontera
A MILLIKEN COMPANY